

RS AFC or RS AFW Adjustable Frame for Basketball Backstops:

SUPPLY & INSTALL:

RS AFC or RS AFW Adjustable frame as supplied by Royal Stewart Ltd.

Fixed frame structure shall be made from 10 ga. HRMS bent sheet steel. With a mounting pattern of 35" (889 mm) x 20" (508 mm).

Moveable frame structure shall be made from 10 ga. HRMS bent sheet steel and guided by $\frac{1}{2}$ " thick UHMW-PE bushings. With $\frac{3}{4}$ " acme threaded rod adjustable to a maximum travel of 24", c/w HD U hook to accept an auger type handle; and shall adjust goal height from 96" (2439 mm) to 120" (3048 mm).

Frame shall be Electrostatic coated black industrial enamel.

Include one (1) RS HC – Hand Crank for every 2 adjustable frames

Choose from the following models as needed:

- o RS AFC35 Adjustable Frame for Ceiling Mounted Backstop w/ 35" c/c front mount backboard
- o RS AFC63 Adjustable Frame for Ceiling Mounted Backstop w/ 63" c/c front mount backboard
- o RS AFW35 Adjustable Frame for Wall Mounted Backstop w/ 35" c/c front mount backboard
- o RS AFW63 Adjustable Frame for Wall Mounted Backstop w/ 63" c/c front mount backboard